



F&D

O'CONNOR PTY LTD

Lightweight Conveyor Belting and Power Transmission Specialists

Chrome Leather Belting



Kronite

F&D

O'CONNOR PTY LTD

www.fdoconnor.com.au

15 PELMET CRESCENT
THOMASTOWN VIC 3074
AUSTRALIA

PHONE: (03) 9462 4544
FAX: (03) 9462 4744
EMAIL: belts@fdoconnor.com.au

www.fdoconnor.com.au

15 PELMET CRESCENT
THOMASTOWN VIC 3074
AUSTRALIA

PHONE: (03) 9462 4544
FAX: (03) 9462 4744
EMAIL: belts@fdoconnor.com.au

Chrome Leather Belting

	LNF 60	LNF 100	LNF 120	LNF200	LNL 60	LNL100	LNL 120	LNL200
Thickness (mm)	2.2	2.5	3	4.3	3	3.3	4.1	5.9
Weight (kg/m ²)	2.8	3.2	3.6	4.6	3.7	4.4	4.9	6.1
Max Width (mm)	500	500	500	500	500	500	500	500
Min Pulley Diameter (mm)	35	70	85	150	35	70	85	150
Minimum Back Flex (mm)	N/A	N/A	70	120	N/A	N/A	N/A	N/A
Load for 1% Elongation (N/mm)	7	10	12	18	7	10	12	18
Min Operating Temp (°C)	-30	-30	-30	-30	-30	-30	-30	-30
Max Operating Temp (°C)	80	80	80	80	80	80	80	80
Outer Side Material	Leather Chrome	Leather Chrome	Leather Chrome	Leather Chrome	Leather Chrome	Leather Chrome	Leather Chrome	Leather Chrome
Outer Side Colour	Grey	Grey	Grey	Grey	Grey	Grey	Grey	Grey
Underside Material	Fabric	Fabric	Fabric	Fabric	Fabric	Fabric	Fabric	Fabric
Underside Feature	Poly. Skim	Poly. Skim	Poly. Skim	Poly. Skim	Poly. Skim	Poly. Skim	Poly. Skim	Poly. Skim
Underside Colour	Green	Green	Green	Green	Green	Green	Green	Green
Co-efficient of Friction (u)	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
Food Approval	NO	NO	NO	NO	NO	NO	NO	NO

