

STRUCTURE

Total thickness	2.5mm
No. of plies	2
Fabric	Polyester
Weft	Rigid
Weight	2.7kg/m ²
Working Temp. min.	-10°C
Working Temp. max.	+80°C



1. Top cover

Top cover thickness	0.7mm
Material	PVC
Colour	Black
Surface	Matt
Hardness	80 shore A

2. Internal cover

Material	PVC
Material	Polyester
Colour	White/Natural
Surface	Bare Fabric

TENSIONS

Working load 1% elongation	8N/mm
Max. Working Tension	12N/mm

MIN. DRUM DIAMETER

Flexing	60mm
Back Flexing	80mm

JOIN TYPE

A40LLSS, RS62SS, Finger Splice

PROFILES APPLICATION

Profile on top Cover	Yes
Profile on bottom cover	Yes
Runner Sidewalls	Yes

SPECIAL CHARACTERISTICS

General Purpose	Yes
Abrasion resistance	Yes
Flame retardant	No
FDA Approved	No
EU Approved	No
Antistatic	Yes

SUPPORT SURFACE

Slider bed	Yes
Rollers	Yes
Troughed Application	No

COEFFICIENT OF FRICTION

Steel driving pulley	0.31
Plastic slider bed	0.25

The user is responsible for proper selection and use of the product taking into consideration its commercial and industrial needs. Values shown are typical and are subject to change without notice. Specifications are subject to change without notice. Weight tolerance g/m² + or - 5% variation.

For more information, please call 03 9462 4544 or email us on sales@fdoconnor.com.au