


STRUCTURE

Total thickness	4.0mm
No. of plies	3
Fabric	Polyester
Weft	Rigid
Weight	4.8kg/m ²
Working Temp. min.	-10° C
Working Temp. max.	+80° C



1. Top cover

Top cover thickness	1.1mm
Material	PVC
Colour	Green
Surface	Glossy
Hardness	75 shore A

2. Internal cover

Material	PVC
----------	-----

3. Bottom cover

Material	Polyester
Colour	White/Natural
Surface	Bare Fabric

PROFILES APPLICATION

Profile on top Cover	Yes
Profile on bottom cover	Yes
Runner Sidewalls	Yes

SPECIAL CHARACTERISTICS

General Purpose	Yes
Abrasion resistance	Yes
Flame retardant	No
FDA Approved	No
EU Approved	No
Antistatic	Yes

TENSIONS

Working load 1% elongation	13N/mm
Max working tension	24N/mm

SUPPORT SURFACE

Slider bed	Yes
Rollers	Yes
Troughed Application	No

MIN. DRUM DIAMETER

Flexing	800mm
Back Flexing	100mm

COEFFICIENT OF FRICTION

Steel driving pulley	0.11
Plastic slider bed	0.16

JOIN TYPE

RS125, O/Lap Splice

The user is responsible for proper selection and use of the product taking into consideration its commercial and industrial needs. Values shown are typical and are subject to change without notice. Specifications are subject to change without notice. Weight tolerance g/m² + or - 5% variation.

For more information, please call 03 9462 4544 or email us on sales@fdoconnor.com.au