



# BB30/95 DE SOLID P/U

## STRUCTURE

Total thickness	3mm
Fabric	Solid P/U
Weight	3.5kg/m <sup>2</sup>
Temperature min.	-20° C
Temperature max.	+70° C



## CONSTRUCTION

Hardness	95 Shore A
Top Surface	Gloss
Bottom Surface	Diamond Pattern
	Low Friction
Colour	Blue or Ivory

## PROFILES APPLICATION

Profile on top Cover	Yes
Profile on bottom cover	Yes
Runner Sidewalls	Yes

## TENSIONS

Working load 1% elongation	1.8N/mm
----------------------------	---------

## SPECIAL CHARACTERISTICS

Minerals, Oils & Grease Res.	Yes
Cut & Abrasion Res.	Yes
FDA Approved	Yes
USDA Approved	Yes

## MIN. DRUM DIAMETER

Flexing	45mm
Back Flexing	60mm

## SUPPORT SURFACE

Slider bed	Yes
Rollers	Yes
Troughed Application	Yes

## JOIN TYPE

Finger Splice, Welding rod, Fasteners

## APPLICATION

Use in high contamination environments  
 Suitable for dairy, meat & poultry industries  
 Suitable for brick, tile, timber & steel industries  
 Highly Sanitary

The user is responsible for proper selection and use of the product taking into consideration its commercial and industrial needs. Values shown are typical and are subject to change without notice. Specifications are subject to change without notice. Weight tolerance g/m<sup>2</sup> + or - 5% variation.

For more information, please call 03 9462 4544 or email us on [sales@fdoconnor.com.au](mailto:sales@fdoconnor.com.au)