

STRUCTURE

Total thickness	1.5mm
No. of plies	2
Fabric	Polyester
Weft	Rigid
Weight	1.3kg/m ²
Constant temp. min	-40° C
Constant temp. max.	+100° C



1. Top cover

Top cover thickness	0.2mm
Material	Polyurethane
Colour	White
Surface	Matt
Hardness	86 shore A

2. Internal cover

Material	Polyurethane
----------	--------------

3. Bottom cover

Material	Polyurethane
Colour	White
Surface	Polyester IMPGR.

TENSIONS

Working load 1% elongation	8N/mm
Breaking load	16N/mm

MIN. DRUM DIAMETER

Flexing	12mm
Back Flexing	25mm

FASTENERS

G001SS, G002SS, A40LLSS
A40SP-SS, RS62SS

PROFILES APPLICATION

Profile on top Cover	Yes
Profile on bottom cover	Yes
Runner Sidewalls	Yes

SPECIAL CHARACTERISTICS

Minerals, Oils & Grease Res.	Excellent
Abrasion resistance	Good
Chemical resistance	Excellent
Flame retardant	No
FDA Approved	Yes
USDA Approved	Yes
EU Approved	Yes
Antistatic	No

SUPPORT SURFACE

Slider bed	Yes
Rollers	Yes
Troughed Application	No

COEFFICIENT OF FRICTION

Steel driving pulley	0.25
Lagged driving pulley	0.35
Stainless slider bed	0.15
Plastic slider bed	0.25