

STRUCTURE

Total thickness	1.8mm
No. of plies	2
Fabric	Polyester
Weft	Non-rigid
Weight	1.9kg/m ²
Constant temp. min	-10° C
Constant temp. max.	+80° C



1. Top cover

Top cover thickness	0.2mm
Material	Polyurethane
Colour	Blue
Surface	Matt
Hardness	87 shore A

2. Internal cover

Material	Polyurethane
----------	--------------

3. Bottom cover

Material	Polyurethane
Colour	White/Natural
Surface	Polyester IMPGR.

PROFILES APPLICATION

Profile on top Cover	Yes
Profile on bottom cover	Yes
Runner Sidewalls	Yes

SPECIAL CHARACTERISTICS

Minerals, Oils & Grease Res.	Yes
Flame retardant	No
FDA Approved	Yes
EU Approved	Yes
ATEX Approved	No
Curve conveyor suitable	Yes

TENSIONS

Working load 1% elongation	15N/mm
Breaking load	20N/mm

SUPPORT SURFACE

Slider bed	Yes
Rollers	Yes
Troughed Application	Yes

MIN. DRUM DIAMETER

Flexing	10mm
Back Flexing	40mm

COEFFICIENT OF FRICTION

Steel driving pulley	0.15
----------------------	------

JOIN TYPE

G00SS, Finger splice

The user is responsible for proper selection and use of the product taking into consideration its commercial and industrial needs. Values shown are typical and are subject to change without notice. Specifications are subject to change without notice. Weight tolerance g/m² + or - 5% variation.

For more information, please call 03 9462 4544 or email us on sales@fdoconnor.com.au