


STRUCTURE

Total thickness	1.3mm
No. of plies	2
Fabric	IMPGR. Fabric
Weft	Rigid
Weight	1.4kg/m ²
Constant temp. min	-30° C
Constant temp. max.	+80° C



1. Top cover

Top cover thickness	0.25mm
Material	Polyurethane
Colour	Green
Surface	Matt
Hardness	90 shore A

2. Internal cover

Material	Polyurethane
----------	--------------

3. Bottom cover

Material	Polyurethane
Colour	White/Natural
Surface	Polyester IMPGR.

TENSIONS

Working load 1% elongation	8N/mm
Breaking load	12N/mm

MIN. DRUM DIAMETER

Flexing	20mm
Back Flexing	40mm

JOIN TYPE

G00SS, Finger Splice

PROFILES APPLICATION

Profile on top Cover	Yes
Profile on bottom cover	Yes
Runner Sidewalls	No

SPECIAL CHARACTERISTICS

Minerals, Oils & Fats Res.	Yes
Abrasion resistance	Yes
Flame retardant	No
FDA Approved	Yes
EU Approved	Yes
ATEX Approved	No
Antistatic	Yes

SUPPORT SURFACE

Slider bed	Yes
Rollers	Yes
Troughed Application	No
Sliding on return side	No

COEFFICIENT OF FRICTION

Steel driving pulley	0.20
Lagged driving pulley	0.20

The user is responsible for proper selection and use of the product taking into consideration its commercial and industrial needs. Values shown are typical and are subject to change without notice. Specifications are subject to change without notice. Weight tolerance g/m² + or - 5% variation.

For more information, please call 03 9462 4544 or email us on sales@fdoconnor.com.au